



Premium Passthrough Dishwashers



Introducing the new Premium Range Passthroughs from DC, specifically designed to meet the rigorous demands of all UK catering outlets.



- **Fast**
- **Heavy Duty**
- **Energy Efficient**
- **Economical**



Performance

Fast, powerful wash cycle
for maximum productivity and deep cleaning

Hood auto-start
increases speed and productivity and reduces user intervention

Heavy duty heater elements
faster start up and improved heat recovery times

Rinse thermo-lock
delivers perfect rinse temperatures time after time

Increased usable height
accommodates larger items such as trays, pots and utensils

Energy and Cost Savings

Low volume wash tank
reduces water consumption and chemical costs

Reduced electrical costs
low water usage requires less energy to heat the machine

Double skinned hood
further reduces noise and heat emissions lowering running costs

Improved rinse arms
increases initial response by 30% and rotation speed by 20%

Insulated boiler
improves heat retention and boiler recovery times

Operation

Intuitive, simple controls
reduces user error and staff training

EasyClean filter system
three stage filter removes debris and protects vital components

Temperature read-outs
wash and boiler temperature read-outs assist machine management

Chemical auto-dosing (optional)
eliminates user intervention and prevents over or under dosing

Integral water softener (optional)
softens water without the need for an external unit

Welcome to a Cleaner World

Premium Range Passthrough Specifications



	PD1000	PD1300	PD1350
Cycle time	120/180 sec	60/120/180 sec	60/120/180 sec
Baskets (x3)	500 x 500 mm	500 x 500 mm	500 x 500 mm
Height	1500 mm	1500 mm	1500 mm
Height - hood raised	1965 mm	1965 mm	1965 mm
Width	655 mm	655 mm	655 mm
Width including handle	745 mm	745 mm	745 mm
Depth	745 mm	745 mm	745 mm
Usable wash height	435 mm	435 mm	435 mm
Drain height	470 mm	410 mm	410 mm
Drain diameter Ø	32 mm	32 mm	32 mm
Wash tank	22 L	28 L	28 L
Boiler	5 L	5 L	9 L
Water usage	2.4 L p/c	2.4 L p/c	2.4 L p/c
Wash element	3.0 kW	3.0 kW	3.0 kW
Boiler element	6 kW	6 kW	10 kW
Total load	6.75 kW	6.75 kW	11.1 kW
Amps required	32 Amps*	32 Amps*	3N 18 Amps
Detergent dosing	Yes	Yes	Yes
Rinse aid dosing	Yes	Yes	Yes
Water connection	3/4 BSP	3/4 BSP	3/4 BSP
Required water pressure	2-4 bar	2-4 bar	2-4 bar
Required water flow rate	10 L p/min	10 L p/min	10 L p/min
Drain pump	Optional	Optional	Optional
Internal softener*	Optional	Optional	Optional
Break tank (WRAS)	Optional	Optional	Optional



Where water hardness exceeds 100ppm a water softener is required.

* Can be configured to operate on either 20A or 3Ph+N upon request.

** Internal water softener is not suitable for hot water above 30°C. Softening capacity between regenerations is 250 litres @ 300ppm. Where water hardness exceeds 300ppm and the daily wash cycles exceed 80 per day an alternative softener may be required - please contact your supplier for further information.

Warranty: One year parts and labour. Extended warranties available - please ask your supplier.

We reserve the right to change specifications without notice.



DC Products

Unit 25 Lodge Hill Industrial Park, Westbury Sub Mendip, Somerset, BA5 1EY

t: +44 (0)1749 870055 f: +44 (0)1749 870056 e: sales@dcproducts.co.uk www.dcprouducts.co.uk

